

D-Link DAP-2360

Home Maintenance Configuration System Logout Help

DAP-2360

- Basic Settings
 - Wireless
 - LAN
 - IPv6
- Advanced Settings
- Status

Wireless Settings

Wireless Band	2.4GHz				
Mode	Access Point				
Network Name (SSID)	TSS				
SSID Visibility	Enable				
Auto Channel Selection	Enable				
Channel	6				
Channel Width	Auto 20/40 MHz				
Authentication	WPA-Personal				
PassPhrase Settings					
WPA Mode	AUTO (WPA or WPA2)				
Cipher Type	Auto	Group Key Update Interval	360000 (Sec)		
<input checked="" type="radio"/> Manual	<input type="radio"/> Periodical Key Change				
Activated From	Sun	:	00	:	00
Time Interval	1 (1~168)hour(s)				
PassPhrase				
Confirm PassPhrase				

notice: 8~63 in ASCII or 64 in Hex.
(0-9,a-z,A-Z,~!@#%&*()_+`-={}|:~|./<>?)

Save

1번 AP 설정

Home Maintenance Configuration System Logout Help

DAP-2360

- Basic Settings
 - Wireless
 - LAN
 - IPv6
- Advanced Settings
- Status

LAN Settings

Get IP From	Static IP (Manual)
IP Address	192.168.0.240
Subnet Mask	255.255.255.0
Default Gateway	192.168.0.1
DNS	203.248.252.2

Save

- DAP-2360
 - Basic Settings
 - Wireless
 - LAN
 - IPv6
 - Advanced Settings
 - Performance
 - Wireless Resource
 - Multi-SSID
 - VLAN
 - Intrusion
 - Schedule
 - Internal RADIUS Server
 - ARP Spoofing Prevention
 - Bandwidth Optimization
 - AP Array
 - Captive Portal
 - DHCP Server
 - Filters
 - Traffic Control
 - Status

Performance Settings

Wireless band	2.4GHz ▾
Wireless	On ▾
Wireless Mode	Mixed 802.11n, 802.11g and 802.11b ▾
Data Rate	Best(Up to 300) ▾ (Mbps)
Beacon Interval (40-500)	100
DTIM Interval (1-15)	1
Transmit Power	100% ▾
WMM (Wi-Fi Multimedia)	Enable ▾
Ack Time Out (2.4GHz, 48~200)	48 (μs)
Short GI	Enable ▾
IGMP Snooping	Disable ▾
Multicast Rate	Disable ▾ (Mbps)
Multicast Bandwidth Control	Disable ▾
Maximum Multicast Bandwidth	100 kbps
HT20/40 Coexistence	Enable ▾
Transfer DHCP Offer to Unicast	Disable ▾

Save

DAP-2360

- Basic Settings
 - Wireless
 - LAN
 - IPv6
- Advanced Settings
- Status

Wireless Settings

Wireless Band: 2.4GHz

Mode: Access Point

Network Name (SSID): TSS_R&D

SSID Visibility: Enable

Auto Channel Selection: Enable

Channel: 6

Channel Width: Auto 20/40 MHz

Authentication: WPA-Personal

PassPhrase Settings

WPA Mode: AUTO (WPA or WPA2)

Cipher Type: Auto Group Key Update Interval: 360000 (Sec)

Manual Periodical Key Change

Activated From: Sun : 00 : 00

Time Interval: 1 (1~168)hour(s)

PassPhrase:

Confirm PassPhrase:

notice: 8~63 in ASCII or 64 in Hex.
(0-9,a-z,A-Z,~!@#\$\$%^&*()_+`-={}|:~!./<>?)

Save

2번 AP 설정

DAP-2360

- Basic Settings
 - Wireless
 - LAN
 - IPv6
- Advanced Settings
- Status

LAN Settings

Get IP From: Static IP (Manual)

IP Address: 192.168.0.241

Subnet Mask: 255.255.255.0

Default Gateway: 192.168.0.1

DNS: 203.248.252.2

Save